



STREAMLIGHT



PROTAC® HL-X FLASHLIGHT

Multi-Fuel 1,300 Lumen Tactical Flashlight

The 1,300 lumen ProTac HL-X is a tactical handheld flashlight that is available in two configurations: rechargeable, with our Streamlight SL-B26 protected Li-Ion USB rechargeable battery pack, or non-rechargeable, with two CR123A lithium batteries.

- **Multi-Fuel:** Uses (1) rechargeable Streamlight [SL-B26 protected Li-Ion USB rechargeable battery pack](#) or (2) CR123A lithium batteries
 - **Rechargeable system** includes (1) SL-B26 battery pack, USB cord, and nylon holster
 - **Non-rechargeable system** includes (2) CR123A lithium batteries and nylon holster
- **TEN-TAP Programming - Choice of Three User-Selectable Programs:**
 - 1) High/Strobe/Low 2) High Only 3) Low/Medium/High
- **Output:**
 - **High:** 1,300 lumens; 35,000 candela; 374m beam; runs 1.5 hours (SL-B26) // 1.25 hours (CR123A)
 - **Medium:** 420 lumens; 11,000 candela; 210m beam; runs 3.75 hours (SL-B26) // 3 hours (CR123A)
 - **Low:** 70 lumens; 1,800 candela; 85m beam; runs 25 hours (SL-B26) // 20 hours (CR123A)
 - **Strobe:** runs 3.25 hours (SL-B26) // 2.5 hours (CR123A)
- Durable, anodized aluminum construction; unbreakable pocket clip
- **IP68-rated;** dust tight and waterproof to 2m; all openings O-ring sealed
- 2-meter impact resistance tested
- Anti-roll head
- **Length:** 5.43 in (13.8 cm)
- **Weight:** 5.7 oz (162g) with **CR123A**; 6.2 oz (176g) with **SL-B26** battery pack
- **TAA compliant models available**

Product Specifications

Battery Type

SL-B26 Rechargeable Battery Pack, CR123A Lithium

Battery Quantity (Min)

1

Battery Quantity (Max)

2

Length (Max)

5.43 inches (13.79 centimeters)

Weight (Max)

6.20 ounces (175.77 grams)

Weight (Min)

5.70 ounces (161.59 grams)

Colors

Black

Lumens (High) [SL-B26]

1,300

Lumens (Medium) [SL-B26]

420

Lumens (Low) [SL-B26]

70

Run Time (High) [SL-B26]

1.50

Run Time (Medium) [SL-B26]

3.75

Run Time (Low) [SL-B26]

25.00

Strobe Run Time [SL-B26]

3.25

Beam Distance (High) [SL-B26]

374

Beam Distance (Medium) [SL-B26]

210

Beam Distance (Low) [SL-B26]

85

Candela (High) [SL-B26]

35,000

Candela (Medium) [SL-B26]

11,000

Candela (Low) [SL-B26]

1,800

Lumens (High) [CR123A]

1,000

Lumens (Medium) [CR123A]

400

Lumens (Low) [CR123A]

65

Run Time (High) [CR123A]

1.25

Run Time (Medium) [CR123A]

3.00

Run Time (Low) [CR123A]

20.00

Strobe Run Time [CR123A]

2.50

Beam Distance (High) [CR123A]

330

Beam Distance (Medium) [CR123A]

200

Beam Distance (Low) [CR123A]

80

Candela (High) [CR123A]

27,100

Candela (Medium) [CR123A]

10,000

Candela (Low) [CR123A]

1,600