



STINGER DS® LED FLASHLIGHT

All Purpose, Rechargeable Dual Switch Flashlight

This aluminum body flashlight is designed with a head-mounted switch and a tail switch for maximum flexibility. Use it on high for a bright beam with a 322 meter beam distance, or switch it to low for a 10 hour run time to last throughout your shift.

- Both a tail cap and a head-mounted switch. Switches operate independently.
- **Three Modes and Strobe:**
 - **High for a Super-Bright Beam:** 425 lumens; 322 meter beam; runs 3 hours; 26,000 candela
 - **Medium for Bright Light and Longer Run Times:** 200 lumens; 219 meter beam; runs 5.5 hours; 12,000 candela
 - **Low for Light Without Glare and Extended Run Times:** 100 lumens; 155 meter beam; runs 10 hours; 6,000 candela
 - **Strobe:** runs 7.5 hours
- Durable aluminum body with non-slip rubberized comfort grip
- **IPX4** water-resistant; 1 meter impact resistance tested
- Rechargeable NiMH battery
- Steady charge, smart charge, or **PiggyBack** charger options
- Anti-roll rubber ring included
- Unbreakable polycarbonate lens with scratch-resistant coating
- **Length:** 8.85 " (22.48 cm); **Weight:** 12.8 oz (364 grams)
- Serialized for positive identification
- **Limited lifetime warranty**

 The shape, style and appearance of the generally triangular feature on the head of the Stinger DSLED is a trademark of Streamlight, Inc.

Product Specifications

Lumens (High)

425

Lumens (Medium)

200

Lumens (Low)

100

Run Time (High)

3.00

Run Time (Medium)

5.50

Run Time (Low)

10.00

Strobe Run Time

7.50

Beam Distance (High)

322

Beam Distance (Medium)

219

Beam Distance (Low)

155

Candela (High)

26,000

Candela (Medium)

12,000

Candela (Low)

6,000

Battery Type

Nickel-Metal Hydride

Battery Quantity (Max)

1

Length (Max)

8.85 inches (22.48 centimeters)

Weight (Max)

12.80 ounces (362.87 grams)

Colors

Black