



SURVIVOR PIVOT® :: RECHARGEABLE OR ALKALINE

Intrinsically Safe Class I, Div. 1 Rated Flashlight

The Survivor Pivot features a dual beam and a 90° articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.

- **Class 1, Div. 1 Rated**
- Available in Rechargeable and Alkaline models
- **LED Technology with Various Lighting Modes:**
 - **Rechargeable Model (High Mode)**
 - **Spot:** 300 lumens; 369m beam distance; runs 4.25 hours
 - **Flood:** 300 lumens; 35m beam distance; runs 4.25 hours
 - **Spot/Flood Combo:** 325 lumens; 276m beam distance; runs 3.75 hours
 - **Alkaline Model (High Mode)**
 - **Spot:** 300 lumens; 369m beam distance; runs 5.5 hours
 - **Flood:** 300 lumens; 35m beam distance; runs 5.5 hours
 - **Spot/Flood Combo:** 325 lumens; 276m beam distance; runs 4.5 hours
- 3.4 Ahr lithium-ion battery pack rechargeable up to 1,000 times. Also accepts (3) AA alkaline batteries (requires optional battery carrier)
- Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward-hanging orientation
- Optional removable grade N45 magnet with 30 lb pull strength
- Rubber dome push-button switch provides easy operation even when wearing heavy gloves; features battery status indicator
- High-impact, super-tough polymer construction offers exceptional durability
- Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel
- **IP67-rated;** dust-tight and waterproof to 1 meter for 30 minutes
- 2-meter impact resistance tested
- **Height x Width:** 7.93 in x 2.86 in (20.14 cm x 7.26 cm)
- Weight ranges from 16.2 oz to 18.1 oz (459 g to 513 g), depending on model
- **Limited lifetime warranty**
- **THE PRODUCT SPECIFICATIONS BELOW REFER TO THE RECHARGEABLE MODEL ONLY**

Note: The Survivor Pivot is not compatible with legacy Survivor chargers.

WARNING—EXPLOSION RISK, BURN, AND FIRE HAZARD. Do not use SL-B9 or SL-B34 batteries in firefighting apparatus or fire situations. Do not expose SL-B9 or SL-B34 battery to temperatures greater than 140°F (60°C).

Product Specifications

Lumens (High)

325

Lumens (Low)

80

Run Time (High)

3.75

Run Time (Low)

13.00

Beam Distance (High)

276

Beam Distance (Low)

141

Candela (High)

19,000

Candela (Low)

5,000

Battery Type

Lithium Ion Cell Pack, AA Alkaline

Length (Max)

7.93 inches (20.14 centimeters)

Weight (Max)

1 pounds 2.10 ounces (513.13 grams)

Weight (Min)

1 pounds 0.20 ounces (459.26 grams)

Colors

Orange, Yellow

Lumens (High) [Flood]

300
Lumens (Low) [Flood]
70
Run Time (High) [Flood]
16.00
Run Time (Low) [Flood]
4.25
Beam Distance (High) [Flood]
35
Beam Distance (Low) [Flood]
17
Candela (High) [Flood]
8,500
Candela (Low) [Flood]
300
Run Time (High) [Flood - Alkaline]
5.50
Run Time (Low) [Flood - Alkaline]
15.00
Lumens (High) [Spot]
300
Lumens (Low) [Spot]
70
Run Time (High) [Spot]
4.25
Run Time (Low) [Spot]
16.00
Beam Distance (High) [Spot]
369
Beam Distance (Low) [Spot]
184
Candela (High) [Spot]
34,000
Candela (Low) [Spot]
8,500
Run Time (High) [Spot - Alkaline]
5.50
Run Time (Low) [Spot - Alkaline]
15.00